

Via Caduti della Liberazione, 57 21040 Uboldo (VA) – Italia Tel: +39 02 964121 Fax: +39 02 96412294

Web: www.eurocel.it

PRODUCT INFORMATION **EUROCEL MSK 6085**

DESCRIPTION

Masking tape UV and weather resistant.

PRODUCT DATA

Backing	74 g/m² UV resistant waterproof saturated paper; blue		
Adhesive	Acrylic water based		

	Unit	Value	Method
Total thickness	mm	0.130	PSTC 133
Adhesion to steel	N/25mm	3.75	PSTC 101
Tensile strength MD	N/25mm	90	PSTC 131
Elongation at break	%	8.5	PSTC 131
Temp. Resistance	°C	n.a.	=

APPLICATION

Blue masking tape recommended for light outdoor applications and also internal applications where surfaces are exposed to UV rays and moisture. Recommended to remove within 7 days.

Features	Benefits			
Acrylic water based adhesive	✓ Good adhesion level ✓ UV and weather resistant ✓ Easy removal without adhesive residue up to 7 days ✓ UV and weather resistant ✓ Easy unwinding			
Water resistant saturated paper backing	 ✓ Water resistant ✓ Well adaptable to most shaped surfaces ✓ Compatible with most common paints ✓ Removable without breaking ✓ Hand tearable 			

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.